

GSM-M



Cellular communicator

The GSM unit provides an alternative, wireless, route to your central station in the event of landline failure. It also allows users to remotely contact their HKC System using a mobile phone. Features include: Alarm alerts texted directly to a mobile phone; An arm & disarm alarm system and; An events log and a system status report.

It can be integrated with customers' home automation systems to turn on and off lights, heating etc. It can also open and close gates. The GSM-P comes in an ABS housing

GSM-M

- Telephony through PSTN or GSM network
- Pre-fitted SIM for access to O₂ Wireless Network
- Control HKC System via mobile phone
- GSM dual band (900MHz & 1800MHz)
- 2 inputs including a "Force GSM Call" input
- 4 programmable outputs
- 2400 baud printer port (N,8,1)
- Connects to our SecureWave panels
- Can operate in Standalone Mode
- Quiescent Current: 100mA
- Current during call: 550mA
- Weight: 3,330g
- Size: 360mm x 236mm x 86mm
- EN 50131-1
- EN Grade 2
- Environmental Class II

EN 1A/12V PSU

- Fully addressable through ID bus
- Automatically monitored
- 2 programmable relay outputs
- Deep discharge protection
- Can operate in Standalone Mode
- Size: 360mm x 236mm x 86mm
- EN 50131-6
- EN Grade 2
- Environmental Class II



SecureWave
868MHz Radio

Safe & Secure

www.hkc.ie

Security

GSM-P



Cellular communicator

The GSM unit provides an alternative, wireless, route to your central station in the event of landline failure. It also allows users to remotely contact their HKC System using a mobile phone. Features include: Alarm alerts texted directly to a mobile phone; An arm & disarm alarm system and; An events log and a system status report.

It can be integrated with customers' home automation systems to turn on and off lights, heating etc. It can also open and close gates. The GSM-P comes in an ABS housing

GSM-P

- Telephony through PSTN or GSM network
- Pre-fitted SIM for access to O₂ Wireless Network
- Control HKC System via mobile phone
- ABS housing
- GSM dual band (900MHz & 1800MHz)
- 2 inputs including a "Force GSM Call" input
- 4 programmable outputs
- 2400 baud printer port (N,8,1)
- Connects to our SecureWave panel
- Quiescent Current: 100mA
- Current during call: 550mA
- Weight: 475g
- Size: 236mm x 166mm x 42mm
- EN 50131-1
- EN Grade 2
- Environmental Class II



SecureWave
868MHz Radio

Safe & Secure

Thank you for considering HKC products for your security system.

For further information in relation to any of our products, please contact us at:

HKC Ltd.
Parkway Business Centre, Ballymount,
Dublin 24, Ireland.
T: 353 1 456 7007
F: 353 1 456 8332
E: sales@hkc.ie
UK Technical Support: 0800 111 4599

or visit us at www.hkc.ie

www.hkc.ie

Security